



## SolarEdge PowerBox™ Module Add-On Box Solution



### A superior approach to maximizing the throughput of photovoltaic systems using module embedded electronics

- Up to 25% increase in power output
- Flexible system design & installation
- Next generation maintenance with module level monitoring and smart alerts
- Unprecedented installer and firefighter safety
  
- The most cost effective solution for residential, commercial and large field installations
- Designed for any crystalline silicon module



architects of energy™

# SolarEdge PowerBox™

## Module Add-On Box Solution

PB250-AOB  
PB350-AOB

### HIGHLIGHTS

- Add-On PowerBox installed on each panel
- Lower installation costs with faster design, less wiring, diodes, fuses and better maintenance
- Module-level monitoring - for easy module and string level fault detection with no added wiring
- Immediate installation feedback for quick commissioning
- Unprecedented installer and firefighter Safety Mode - safe module voltage when inverter is disconnected or off
- Part of SolarEdge's patented Smart-DC system
- Easy no constraint installation – use the same installation methods as exist today with all the SolarEdge added benefits
- Panel level MPPT - optimizes each panel separately
- Allows parallel uneven length strings with no added diodes
- Simplifies panel inventory considerations

### TECHNICAL DATA

INPUT		
Rated Input DC power	250 / 350	W
Absolute Maximum Input Voltage (Voc)	60 (*)	Vdc
MPPT Operating Range	5 - 60	Vdc
Maximum Input Current	10	Adc
Reverse-Polarity Protection	Yes	
Maximum Efficiency	98.6	%
European Weighted Efficiency	97.8	%
CEC Weighted Efficiency	97.7	%
Inductive Lightning Protection	1 / 3	m / ft
Nighttime Power Consumption	0	W
OUTPUT DURING OPERATION (POWERBOX CONNECTED TO OPERATING INVERTER)		
Maximum Output Current	15	Adc
Operating Output Voltage	5 - 60	Vdc
Total Maximum String Voltage (Controlled by Inverter) - US and EU 1-ph	550	Vdc
Total Maximum String Voltage (Controlled by Inverter) - EU 3-ph	950	Vdc
OUTPUT DURING STANDBY (POWERBOX DISCONNECTED FROM INVERTER OR INVERTER OFF)		
Safety Output Voltage per PowerBox	1	Vdc
PV SYSTEM DESIGN		
Minimum Number of PowerBoxes per String	8 (1ph system) / 15 (3ph system)	
Maximum Number of PowerBoxes per String	module power dependant; typically 20 - 25 (1ph system) / 45 - 55 (3ph system)	
Parallel Strings of Different Lengths or Orientations	Yes	
STANDARD COMPLIANCE		
EMC	FCC Part15 Class B, IEC61000-6-2, IEC61000-6-3	
Safety	UL1741, IEC-62103 (class II safety), IEC61730	
Material	UL-94 (5-VA), UV Resistant	
RoHS	Yes	
INSTALLATION SPECIFICATIONS		
Dimensions (WxLxH)	149.5x142x27.2 / 5.9x5.6x1.1	mm / in
Weight	800 / 1.8	g / lb
Output PV Wire	1.05 m / 3.6 ft length ; 6 mm <sup>2</sup> ; MC4 compatible	
Input Connector	MC4 compatible / Huber-Suhner / Tyco	
Operating Temperature Range	-40 - +65 / -40 - +150	
Protection Rating	IP65 Outdoor Use / NEMA 3R	
Relative Humidity	0 - 100	%

(\*) TFI version up to 100V

**USA** 900 Golden Gate Terrace, Suite E, Grass Valley CA 95945, USA

**Germany** Königstr. 5, 01097 Dresden, Germany

**Japan** B-9 Ariake Frontier Building, 3-7-26 Ariake, Koto-Ku, Tokyo 135-0063, Japan

**Israel** 6 HaHarash St. P.O.Box 7349, Neve Neeman, Hod Hasharon 45240, Israel



[www.solaredge.com](http://www.solaredge.com)

**solaredge**  
architects of energy™

© Copyright SolarEdge. 2009. All rights reserved. SolarEdge, the SolarEdge logo, PowerBox and architects of energy are trademarks or registered trademarks of SolarEdge, Ltd. All other trademarks mentioned herein are believed to be trademarks of their respective owners. Date: 01/2011. Subject to change without notice.